




# Cytek<sup>®</sup> Aurora CS

Where Cellular Discoveries Take Focus

## Meet Aurora CS



A prodigy built from the Cytek® Aurora system's unique combination of innovative technologies that takes cell sorting to the next level of performance and flexibility.

With up to five lasers, three scattering channels, and 64 fluorescence channels, the Aurora CS is designed to leverage the paradigm-shifting technology onboard the Cytek Aurora and deliver the sorting capabilities you have come to expect in a high-end sorter.

Like Aurora, the CS provides the benefits of full spectrum profiling (FSP™) technology. Its optical design and unmixing algorithm provide scientists increased flexibility, enabling the use of a wide array of new fluorochrome combinations without reconfiguring the system for each application. The state-of-the-art optics and low-noise electronics provide high resolution, high content and high sensitivity.

**The result is a system that delivers high resolution at the single cell level to resolve the most challenging cell populations, such as cells with high autofluorescence or low levels of expression of key biomarkers, regardless of assay complexity, and to isolate live cells for downstream studies. Welcome to a new world where the assays optimized on the Aurora can also be run on the Aurora CS for sorting.**

As a sorter, the CS offers the flexibility required to meet various biological and sorting conditions. With up to 6-way sorting, customizable nozzle settings and sort modes, automated drop delay and sort stream monitoring, the CS offers the flexibility required to meet various application needs from smaller to larger cells.

SpectroFlo® CS software is used to drive the CS. Its sorter UI console offers intuitive workflows combined with powerful and customizable functionality.

In summary, the Aurora CS enables you to take your research even further, gain deeper insights, and accelerate your pace of discovery.

See more. Sort more.


## Built with Cytek's Revolutionary Technologies: Providing Excellent Single Cell Resolution

**The Aurora CS is capable of up to 67 detection channels (64 fluorescence channels, FSC, blue laser SSC, and violet laser SSC) and is empowered by revolutionary technologies, including:**

- Proprietary high sensitivity Coarse Wavelength Division Multiplexing (CWDM) semiconductor detector arrays enable efficient spectrum capture for dyes emitting in the 365–829 nm range.
- High bandwidth electronics design scalable up to 67 channels.
- Integrated HEPA filtration system as a first layer of protection from aerosols.
- Magnetically controlled plate sorting and smooth, easy to clean surfaces.

## Why Choose the Cytek® Aurora CS?

- So Many Colors**  
**40 colors** demonstrated including fluorochromes with emission spectra in close proximity to each other.
- Exceptional Sensitivity and Resolution**  
**Sensitivity redefined** using state-of-the-art optics and low-noise electronics.  
**Extract autofluorescence** and improve resolution of highly autofluorescent samples.
- New Levels of Flexibility**  
**No need to reconfigure optical filters** for different fluorochromes.  
**Use any commercially available fluorochrome** excited by the onboard lasers.  
**Choose from a variety of sample input and collection devices** including 5 and 15 mL tubes for input and 96-well plates, 1.5 and 5 mL tubes for collection.
- Seamless Sorting Experience**  
**Automated drop delay, sort monitoring, and clog detection** for a reliable sorting experience.  
**Comprehensive sort reports** automatically record settings used from every sort.  
**Assay transferability** from the Cytek Aurora system or conventional flow cytometers.



## Feature Highlights

The Cytek® Aurora CS is designed for sorting performance and application flexibility, beginning with sort set-up and carrying through to the sorted sample output. Here are just a few examples. See these and more by requesting a demo with your Cytek technical sales representative ([sales@cytekbio.com](mailto:sales@cytekbio.com)).




### Sample Input Flexibility and Control

The Cytek Aurora CS sample loading chamber accommodates 5 and 15 mL polystyrene or polypropylene tubes. In the SpectroFlo® CS software user interface, the following options are available:

- Toggle on the chamber light to see how much sample remains in the tube
- Choose from three sample tube mixing speeds
- Set the chamber temperature to cool or heat your sample input and sort collection tubes
- After sorting, backflush remaining sample from the sample line into the sample tube to sort as many cells as possible

### Variety of Nozzle Settings

The ideal nozzle diameter for an optimal sort output depends on the size and fragility of the particles of interest. Choose from a 70 or 100µm default nozzle settings or customize and save your own setting inside SpectroFlo CS software for future reuse.



### Predefined and Custom Sort Modes

Select one of Cytek's predefined sort modes or create a custom defined sort mode to meet the needs of each user's sorting application.

#### > Purity

Isolate the population of interest with little to no contaminants from other populations

#### > Enrich

Prioritize retrieving a high number of the target population with reduced sort purity

#### > Multiway

Intended for 4- or 6-way sorting for efficient drop deflection

#### > Single Cell

Isolate single cells into 96-well plates


#### > Mixed

A combination of Purity and Enrich modes

#### > Custom

Adjust the sort decision settings to meet your application needs






## Plate Sorting

Sort into 96-well plates by defining the sort settings for each well inside SpectroFlo® CS software, loading a plate into the plate holder, and placing the holder inside the droplet deposition unit.

Using the plate sorting high throughput mode, deposit 1 cell into 96 wells in less than 2 minutes. Utilize the index sorting feature to track and overlay data from each plate well in the software's analysis plots. Additionally, use the detailed sort reports for a comprehensive record of the sort set-up and performance for each experiment.







## Multi-Way Sorting

Sort up to 6 ways into 1.5 mL tubes, or up to 4 ways into 5 mL tubes. Easily glide the tube holders into the droplet deposition unit, and use integrated live video feed and stream aiming tools inside SpectroFlo CS software to adjust sort streams.



## Biosafety Controls

Primary aerosol evacuation is integrated into the CS with user-replaceable HEPA filters. The timers built into SpectroFlo CS software remind users when to replace the filters.

Warm Up Time Left: 00:15:49 Filter Status  Sheath  19 hrs 30 mins  Waste  Cytometer

SpectroFlo CS software displays instrument indicators for warm up, HEPA filter replacement, remaining sheath, waste tank level, and connection.

For an optional secondary level of protection, add on a small footprint Biosafety Class 2 Type A2 cabinet. The cabinet comfortably houses the CS with room to the right of the instrument for a sample tube rack and other small commonly used laboratory items.


# In-Depth 6-Way Sorting

The Cytek® Aurora CS combines full spectrum profiling (FSP™) technology and high-end sorting functionality to enable you to dig deep into your cellular assays. To demonstrate the Aurora CS's capabilities, made possible by its advanced electronics design, a 28-color human deep T-cell and NK cell immunophenotyping panel was transferred from the Cytek Aurora. Six low frequency T-cell and NK cell subsets shown below were sorted with a 100 µm nozzle and checked for purity.

## 28-Color Human Deep T-Cell and NK Cell Immunophenotyping Panel

UV	Violet	Blue	Yellow-Green	Red
BUV395 CD45RA	BV421 CCR7	FITC CD57	cFluor YG584 CD4	APC CCR4
LIVE/DEAD Blue	BV480 CD62L	Spark Blue 550 CD14	PE/Dazzle 594 CD337	Spark NIR 685 CD56
BUV563 CCR5	BV510 CD3	PerCP CD45	PE-Cy5 CD95	APC-R700 CD127
BUV615 CD314	BV650 CD28	PerCP-eFluor 710 TCRγδ	PE-Alexa Fluor 700 CD25	APC-H7 CD27
BUV661 CD39	BV750 CXCR5		PE-Cy7 TIGIT	APC/Fire 810 CD38
BUV737 CD161	BV785 PD-1		PE/Fire 810 HLA-DR	
BUV805 CD8				

## Sort Populations Defined Deep Into the Gating Hierarchy




The sort gates for each of the six sorted populations are shown in orange in the gating strategy above. The frequency of each sorted population ranged from 0.09 to 0.40% of total cells in the sample. The level in the gating hierarchy for each sort gate is shown by the green rectangle in the upper right corner of each pseudocolor plot, going as deep as 13 levels into the hierarchy.


## Sort Purity Checks

The plots below show the post-sort purity results for each of the six sorted populations.


**CD8<sup>+</sup> TEMRA TIGIT<sup>-</sup> CD57<sup>+</sup>**  
Purity: 99.5%



**CD8<sup>+</sup> TEMRA TIGIT<sup>+</sup> CCR5<sup>+</sup>**  
Purity: 99.7%




**CD4<sup>+</sup> EM TIGIT<sup>-</sup> CCR4<sup>+</sup>**  
Purity: 99.2%




# Take Sorted Cells Into Functional Assays

When sorting cells for downstream experimental assays, it is crucial that the sorted cells remain viable and functional post-sorting. To demonstrate this capability with the Cytek® Aurora CS, human PBMCs were prepared and sorted 4-ways with a 70 µm nozzle to collect CD4+ effector memory, CD8+ effector memory, TCRγδ T cells, and NK cells using the gating strategy below. Sort gates are outlined in orange.

After sorting was completed, the cells were rested for 2 hours in an incubator, then stimulated with PMA and ionomycin in the presence of BFA, monensin, and CD107a, and next stained with 8 different intracellular markers. The results are shown in the high dimensional unsupervised analysis figures below generated using OMIQ and the 2-D plots on the next page generated using SpectroFlo CS software.




## UMAP Plots of FlowSOM Clustered Post-Sort Stimulated Cell Results






## 2-D Plots Post-Sort Cell Functionality Results After PMA/Ionomycin Stimulation


### CD4<sup>+</sup> Effector Memory Cells




### CD8<sup>+</sup> Effector Memory Cells



### TCRγδ T Cells



### NK Cells



Unsorted cells and cells from each of the 4 sorted populations were stimulated with PMA and ionomycin in the presence of BFA, monensin, and CD107a. After stimulation, cells were stained with 8 different intracellular markers. The cells were acquired on a Cytek Aurora system, and the results displayed using 2-D plots in SpectroFlo CS to visualize cell CD107a expression and cytokine production patterns. The cell numbers for each population in the unsorted or sorted populations are different due to the nature of this experiment.

# Resolving Challenging Dye Combinations

The detection of some fluorochrome combinations by conventional flow cytometry presents a challenge due to high amounts of spectral overlap (Figure 1, 4). The Cytek® Aurora CS addresses this challenge by using full spectrum profiling (FSP™) to detect differences in full emission spectra signatures across all lasers to clearly resolve these combinations, even if the populations are co-expressed (Figures 2, 3, 5, and 6).

## Example 1: APC and Alexa Fluor 647




Figure 1: Spectrum plots from a conventional spectrum viewer shows heavy overlap between APC and Alexa Fluor 647.




Figure 2: Spectrum plots from a four-laser Aurora system show distinct signatures for APC and Alexa Fluor 647.




Figure 3: Whole blood from a healthy donor was stained, lysed, washed, and analyzed on a four-laser Aurora system. Subsets of NK and NK T cells that co-express CD56 Alexa Fluor 647 and CD8 APC were easily identified. For comparison, blood from the same donor was stained with CD56 PE and CD8 APC and yielded similar percentages of NK and NK T cells, demonstrating that APC and Alexa Fluor 647 combined did not impact results.

## Example 2: BFP, GFP, and mCherry




Figure 4: Spectrum plots from a conventional spectrum viewer.




Figure 5: Spectrum plots from a four-laser Aurora system show distinct signatures for BFP, GFP and mCherry.





Figure 6: AB2.2 mouse embryonic stem cells were genetically modified to stably express BFP, GFP and mCherry under the control of different fate marker promoters. The stable cell line generated was then cultured under differentiation conditions, harvested, and analyzed on a four-laser Aurora system to assess the expression of fluorescent proteins. Autofluorescence extraction was used to enhance results. Sample courtesy from Luigi Russo, Hannah L. Sladitschek and Pierre Neveu, Cell Biology & Biophysics, Neveu group, EMBL.

# Excellent Optical Performance With Full Spectrum Profiling (FSP™) Technology

The ability to generate high quality multi-parametric data is key to successfully utilize data dimensionality and 2-D visualization algorithms. Cytek's patented FSP technology is built into both the Cytek Aurora system and Cytek Aurora CS so users of both systems can generate high quality data. In OMIP-069 (PMID: 32830910), Cytek's 40-color deep immunophenotyping panel for the Cytek Aurora can perform equally well on the sorting-capable Cytek Aurora CS.

To demonstrate this:

1. 40-color human PBMC samples were prepared.
2. Reference controls and samples were acquired on both the Cytek Aurora system and Cytek Aurora CS.
3. Data from both systems was gated on live singlet CD45<sup>+</sup> lymphocyte and monocyte populations and visualized in 2-D using UMAP.
4. A UMAP scatter plot of the data from each system is shown overlaid below with a high level of comparability. Note the Aurora system (blue) and CS (orange) follow the same patterns and almost fully overlap.
5. UMAP density plots of the data from each system are shown side-by-side.



Have you read OMIP-069? Download it now from the resources publication collection at [cytekbio.com](https://cytekbio.com).

# SpectroFlo® CS Software Acquisition Workflows


SpectroFlo CS software offers an intuitive workflow from quality control (QC) to data analysis with technology-enabling tools that simplify running any application.

### QC and Setup:

Run Daily QC to monitor instrument performance and add reference controls.

### Library:

Add or remove experiment templates, worksheet templates, fluorochrome information, QC bead information, and more.



### Extra Tools:

Unmix data using controls from different experiments or apply virtual filters to your data.

### Users:

For administrative controls.


### Preferences:

Customize the software appearance. Set default plot sizes, text sizes and fonts, gate colors, print layout, statistics table options, and more.

## Experiment Workflow:

From the Acquisition menu, you can start a new experiment and get to your data in four simple guided steps.

### Step 1: Create Your Experiment




Create your experiment, choose fluorochromes, and add labels, tubes, worksheets, and stopping criteria in this guided workflow.

### Step 2: Acquire Your Tubes




Load and run your tubes.

### Step 3: Unmix Your Data



Visualize your reference control spectra with the unmixing wizard.

### Step 4: Analyze Your Unmixed Data




Create an analysis worksheet and save it as a template to reuse and share with others.



# Sort Controls Inside SpectroFlo® CS Software

The Sorter Control window inside SpectroFlo CS software has a variety of controls and guided workflows highlighted below to help each user achieve a successful sort output.



- 1 Enable sample return.
- 2 Select nozzle size, optimize drop break-off and stream settings, and save settings for future use.
- 3 Enable sort monitoring with clog volume detection to help ensure a successful sort.
- 4 Enable sample mixing and temperature control.
- 5 Select tube or plate sort collection device.
- 6 Adjust tube and plate aiming targets and save aim settings for future use.
- 7 Post-sorting, view and export a comprehensive sort report.
- 8 Use the Live View camera feed to help aim streams into the center of each tube and monitor sort tube volumes.
- 9 Click the Auto Drop Delay button to open the automated drop delay wizard.
- 10 Toggle to Adjust Sort Stream or Adjust Drop Delay manually.
- 11 Use the slider and/or manually change values in the text boxes to optimize the center stream.
- 12 Choose a Cytek-defined sort mode or create a custom mode.
- 13 Define population(s) and sort stopping criteria for each plate well or tube.

# Technical Specifications

## Optics

### EXCITATION OPTICS

#### OPTICAL PLATFORM

Aurora CS contains a fixed optical assembly with the capacity to be configured with up to five spatially separated laser beams. Laser delays are automatically adjusted during instrument QC.

#### LASERS

Base model three-laser configuration: 405 nm: 100 mW, 488 nm: 50 mW, 640 nm: 80 mW  
Available laser upgrades: 355 nm: 20 mW, 561 nm: 50 mW

#### BEAM GEOMETRY

Flat-Top laser beam profile with narrow vertical beam height optimized for small particle detection.

### EMISSION OPTICS

#### EMISSION COLLECTION

Fused silica cuvette coupled to high NA lens for optimum collection efficiency to optical fibers.

#### FORWARD AND SIDE SCATTER DETECTION

FSC: high-performance semiconductor detector with 488 nm bandpass filter  
SSC: two high-performance semiconductor detectors with 405 nm and 488 nm bandpass filters

#### FLUORESCENCE DETECTORS

Proprietary high sensitivity Coarse Wavelength Division Multiplexing (CWDM) semiconductor array per laser enabling more efficient spectrum capture in the 365-829 nm range. No filter changes required for any fluorochrome excited by the 355 nm, 405 nm, 488 nm, 561 nm, 640 nm lasers.

#### STANDARD OPTICAL CONFIGURATION

Violet detector module: 16 channels unevenly spaced bandwidth from 420-829 nm.

Blue detector module: 14 channels unevenly spaced bandwidth from 498-829 nm.

Red detector module: 8 channels unevenly spaced bandwidth from 652-829 nm.

4 and 5 Laser Options:

Yellow-Green detector module: 10 channels unevenly spaced bandwidth from 567-829 nm.

Ultraviolet detector module: 16 channels unevenly spaced bandwidth from 365-829 nm.

## Fluidics

### SAMPLE FLOW RATES

Adjustable in increments of 7  $\mu\text{L}/\text{min}$  from 10  $\mu\text{L}/\text{min}$  to 80  $\mu\text{L}/\text{min}$

### FLUIDIC MODES

Fluidics startup, Fluidics shutdown, SIT flush, Purge filter, Clean flow cell, Long clean, Sample line return

### SAMPLE INPUT FORMATS

12x75 mm or 15 mL polystyrene or polypropylene tube with sample mixing

### FLUIDIC RESERVOIRS

10 L sheath and waste fluid containers with level-sensing provided

## Electronics

### SIGNAL PROCESSING

Digital signal processing with automatic window gate adjustment.

22-bit 6.5 log decades.

Threshold using any single parameter or combination of parameters.

### PULSE SHAPE PARAMETERS

Pulse Area and Height for every parameter. Width for scatter parameters and one fluorescence parameter for each laser.

## Workstation

Workstation specifications may vary between laser configuration; below is for three-laser configuration.

### OPERATING SYSTEM

Windows® 10 Pro 64-bit

### PROCESSOR

Intel® Core™ i7 processor, 3.6 GHz

### RAM

64 GB

### HARD DRIVE

500GB SSD and 1 TB SATA

### VIDEO PROCESSOR

NVIDIA® GeForce

### MONITOR

Two 24" UHD 4K Monitors

## Preliminary Performance\*

\*Formal verification pending.

### FLUORESCENCE LINEARITY

FITC  $R^2 \geq 0.995$  / PE  $R^2 \geq 0.995$

### FORWARD AND SIDE SCATTER RESOLUTION

Performance is optimized for resolving lymphocytes, monocytes, and granulocytes.

### SIDE SCATTER RESOLUTION

Capable of resolving 0.1  $\mu\text{m}$  polystyrene beads from noise.

### CARRYOVER

$\leq 0.1\%$

### DATA ACQUISITION RATE

25,000 events/s\*\*

\*\*Five laser system

# Functional Specifications

## Sort Output

### SORT COLLECTION

Up to 4-way sorting: 5 mL, and 1.5 mL polystyrene and polypropylene tubes.

Up to 6-way sorting: 1.5 mL polystyrene and polypropylene tubes.

96-well plates with index sorting.

### NOZZLES

Quick-replace 70 and 100µm nozzles with optimized and user definable pressure and sorter settings.

### SORT MODES

Multiple optimized sort modes for purity, enrichment, mixed, and single cell plus user definable sort modes.

Deposit 1 cell per well into 96 wells in less than 2 minutes.

## Temperature Control

4 to 30°C for both sample input and output.

## Biosafety

### PRIMARY

Built-in aerosol management with user replaceable HEPA filters.

### SECONDARY

Optional Class II, Type A2 Biosafety Cabinet specifically designed for Cytek Aurora Sorter and tested to major worldwide Biosafety Standards with sorter inside.\*

\* Not manufactured by Cytek

## Software

### SPECTROFLO® CS SOFTWARE

Live unmixing during acquisition

Sort on raw or unmixed data

Developed specifically to streamline assay setup, data acquisition, and file export

Automated QC module

Autofluorescence extraction

Automated drop delay module

Default and customizable sort modes and nozzle settings

Sort collection tube volume monitoring and live view

Autogenerated sort reports

Raw and Unmixed FCS 3.1 files

## Regulatory

Class 1 Laser Product.

For Research Use Only. Not for use in diagnostic or therapeutic procedures.

## Installation Requirements

Dimensions (W x D X H)

### INSTRUMENT DIMENSIONS

75 x 57 x 65 cm

### INSTRUMENT WEIGHT

105 kg

### BIO SAFETY CABINET DIMENSIONS

150 x 91 x 231 cm

### RECOMMENDED WORKSPACE

183 x 81 x 94 cm

## Room Requirements

### POWER

100-140 VAC, 15A or 200-250 VAC, 10A

### HEAT DISSIPATION

1000 W with all solid-state lasers

### TEMPERATURE

Outside of Biosafety Cabinet: 18–28°C

Inside Biosafety Cabinet: 18–26°C

### HUMIDITY

20%-85% relative non-condensing

### AIR SUPPLY

551.5 to 586 kPa (80 to 85 PSI) clean dry air

### AIR FILTERING

No excessive dust or smoke

### LIGHTING

No special requirements

## Preliminary Sort Performance\*

\*Formal verification pending.

### SORT PURITY

1%-2% population of lymphocytes using a 70 µm nozzle, mixed sort mode, and a system threshold rate of 20,000 events/second:

Sort purity ≥ 95% and sort yield is ≥ 90% to theoretical yield.

### SORT GATES

Sort up to 6 populations up to 64 levels deep in the gating hierarchy.



Cytek Biosciences is dedicated to enhancing our customers' user experience. The Cytek Aurora CS system is backed by our world-class service and support team that can provide phone or field-based assistance. Various levels of maintenance options are available to meet your needs now, and in the future.

For more information, email us at:  
sales@cytekbio.com or call 1-877-922-9835

## United States

### California

47215 Lakeview Blvd  
Fremont, CA 94538-6407  
1-877-922-9835

### Maryland

4520 East West Highway  
Suite 615  
Bethesda, MD 20814

## China

### Shanghai

560 Shengxia Road, Suite 603  
Zhangjiang High-Tech Park  
Shanghai Pilot Free Trade Zone, 201203  
Tel: 86-21-60897568 | Fax: 86-21-60897570

## Europe

### The Netherlands

Paasheuvelweg 25, Tower C5  
1105 BP Amsterdam  
The Netherlands  
+31 (0) 20 765 3440

## Japan

### Tokyo

"EDGE" Building  
2-9-1 Ikenohata Taito-ku  
Tokyo 110-0008 Japan

The CF® dyes and products incorporating them, such as cFluor™ reagents, are provided under an Agreement between Biotium and Cytek (LICENSEE). The manufacture, use, sale, offer for sale, or import of the product is covered by one or more of the patents or pending applications owned or licensed by Biotium, Inc. (U.S. Patent Nos.) The purchase of this product includes a limited, non-transferable immunity from suit under the foregoing patent claims for using only this amount of product for the purchaser's own internal research. No right under any other patent claim, no right to perform any patented method, and no right to perform commercial services of any kind, including without limitation reporting the results of purchaser's activities for a fee or other commercial consideration, is conveyed expressly, by implication, or by estoppel.

Cytek, cFluor, Full Spectrum Profiling, FSP, and SpectroFlo are trademarks of Cytek Biosciences, Inc. Spark Blue, Spark NIR, PE/Dazzle, and APC/Fire are trademarks and property of BioLegend, Inc. "BV" stands for Brilliant Violet™, which is a trademark of Sirigen Group Ltd. BV480 and APC-R700 are part of the BD Horizon™ brand, which is a trademark of BD Biosciences. BUY395, BUY496, BUY563, BUY661, BUY737 and BUY805 are part of the BD OptiBuild™ and BD Horizon™ Brands, which are registered trademarks of BD Biosciences. APC-H7 is part of the BD Pharmingen™ brand, which is a trademark of BD Biosciences. Alexa Fluor, eFluor, and LIVE/DEAD are trademarks of Thermo Fisher Scientific. Cy and CyDye are registered trademarks of GE Healthcare. Trademarks are the property of their respective owners. Allophycocyanin (APC) conjugates: US Patent No. 5,714,386 PE-Cy7: US Patent No. 4,542,104